

# Broad Temperature Fluid Resistant PSA

## Product Description

Broad-Temperature, Fluid-Resistant (BTFR™) Pressure Sensitive Adhesives (PSAs) from Triton Systems, Inc. (Triton) are derived from a novel chemistry that offers intrinsic fluid resistance and wide use temperature range.

## Triton's Adhesives Offer

- ▶ Broad temperature operating range (-90 to 275 °F)
- ▶ Excellent peel (2 pli to 20+ pli depending on conditions), tensile and shear strengths
- ▶ Excellent fluids resistance
- ▶ Clean peel
- ▶ Repositionability that makes initial placement easy
- ▶ Shelf life of 3 years
- ▶ Customized product forms / tape construction
- ▶ Full commercial manufacturing scale

When used with Triton's adhesion promoter, the PSA is repositionable, either by lifting it off the adhered surface and replacing, or by gently sliding it into place.

We have the ability to balance the properties to specific needs by modifying the chemistry.

## Ability to Customize Product Forms:

- ▶ PSA thickness
- ▶ Tack
- ▶ Carrier film
- ▶ Use temperature
- ▶ Release liner

## Tape Construction

The PSA can be supplied as a transfer tape, a single sided tape, or a double-sided tape. For the single sided and double-sided tape, the carrier film can be chosen from a variety of materials including Kapton and PET. Adhesive thickness can range from 1 mil to 5 mil (0.025 mm to 0.125 mm).



## Physical Properties

Temperature Use Range:..... -90 °F to 275 °F  
..... (-67 °C to 135 °C)

Density:..... 1.102 g/cc

## Sizes

The tape is available in widths up to 59 inches. Roll lengths of 50 to over 1,000 feet are available. Custom widths and lengths are also available.

## Typical Peel Strength

**(180 degree peels on Deft 02-OGN-084 Primed Aluminum, ASTM D3330)**

Fluid	-65 °F	RT	250 °F
None	≥4 lbs/in	≥10 lbs/in	≥2 lbs/in
JP8	≥4 lbs/in	≥10 lbs/in	≥2 lbs/in
Kilfroast	≥4 lbs/in	≥10 lbs/in	≥2 lbs/in
Hydraulic Fluid	≥4 lbs/in	≥10 lbs/in	≥2 lbs/in
Water at 120°F	≥4 lbs/in	≥10 lbs/in	≥2 lbs/in

## Triton Systems, Inc.

330 Billerica Road, Suite 200 Chelmsford, MA 01824

Tel: 781 640-9125 Email: [asingh@tritonsystems.com](mailto:asingh@tritonsystems.com) Web: [www.tritonsystems.com](http://www.tritonsystems.com)

Above values are shown as typical values and should not be used as specifications. © 2022 All rights reserved. Triton System logo is a registered trademark of Triton Systems, Inc.

